



## Product: Super Stick Fumi Tape

Code: C011

### Product Description

Laminated polyethylene cloth, single coated with a high tack ULTRA BOND CLEAR synthetic rubber adhesive.  
Colours: Silver, Pink

### Features

- Ultra High coating weight of adhesive designed to adhere to polyethylene sheeting
- Cloth middle layer helps to facilitate tearing by hand.
- Rubber adhesive helps to resist water and provides for a durable hold.
- Pink colour helps identify that correct tape is used for application.

### Applications

- Joining of polyethylene sheeting in Fumigation industry.
- Shuttering application for construction industry.

### Technical Data

Liner	N/A
Carrier	Polyethylene Coated Cloth
Adhesive	Synthetic Rubber – Clear Ultra Bond.
Film Thickness	70 micron
Adhesive Thickness	85 micron
Total Thickness Allowance (Variance)	155 micron.
Application Temperature	20°C to 25°C
Temperature Resistance	60°C
Sheer Strength	N/A
180° Peel Adhesion (ASTM D 3330)* (Steel)	≥20N/25mm
Holding Power (ASTM D 3654)*	N/A
Tensile Strength (ASTM D 3759)*	≥60N/25mm
Elongation (ASTM D 3759)*	≤10%
Initial Tack (JIS Z0237)*	N/A
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Cool, dry area out of direct sunlight – 12 months