



**Product:** Double Sided Tissue

**Code:** D001

### Product Description

A tissue coated on both sides with a solvent based acrylic adhesive.

### Features

- High initial tack.
- High temperature resistance.
- Long life adhesive.
- Very conformable.

### Applications

- Nameplates & Foam laminations
- Joining plastic and metal components.
- Print finishing of cosmetic packaging, joining of leather, PVC films, fabric jointing, high value PE and Paper Bags

### Technical Data

Liner	Siliconized PE coated paper –white
Carrier	Non-woven tissue
Adhesive	Solvent based acrylic
Film Thickness	14 GSM
Adhesive Thickness	90 GSM
Total Thickness Allowance (Variance)	+/- 10%
Application Temperature	16° - 30°C
Temperature Resistance	-20° - 90°C
Sheer Strength	120 min
180° Peel Adhesion (ASTM D 3330)* (Steel)	≥1.80N/25mm
Holding Power (ASTM D 3654)*	>600mins
Tensile Strength (ASTM D 3759)*	≥6N/cm
Elongation (ASTM D 3759)*	7%
Initial Tack (JIS Z0237)*	13.8N
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Cool, dry area out of direct sunlight – 12 months