



Product: Double Sided PVC

Code: D003/*

Product Description

A clear / white PVC film, coated on both sides with a solvent based acrylic adhesive.

Features

- Offers superior bonding strength and excellent holding power, anti-rebounding & warping
- Offers excellent adhesion at high or low temperatures.
- Superior durability.
- Superior sticking properties for all types of substrates.

Applications

- Metal and plastic component splicing.
- Display nameplates bonding.
- Demanding applications where long term adhesion is required.

Technical Data

Liner	Siliconized PE coated paper – Havana
Carrier	PVC film – white or clear
Adhesive	Solvent based acrylic
Film Thickness	130 Micron
Adhesive Thickness	195 Micron
Total Thickness Allowance (Variance)	+/- 10%
Application Temperature	16° - 30°C
Temperature Resistance	140°C
Sheer Strength	N/A
180° Peel Adhesion (ASTM D 3330)* (Steel)	7.5N/25mm
Holding Power (ASTM D 3654)*	>48 hours
Tensile Strength (ASTM D 3759)*	>6N/cm
Elongation (ASTM D 3759)*	200%
Initial Tack (JIS Z0237)*	N/A
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Cool, dry area out of direct sunlight – 12 months