



**Product:** Double Sided GDA

**Code:** D005

### Product Description

A cloth based tape with a high performance synthetic rubber based adhesive.

### Features

- Very high initial tack.
- Conforms to irregular surfaces.
- Removes easily without leaving residue.
- High coating weight aids adhesion to rough surfaces.

### Applications

- Carpet hold-down for conventions and exhibitions.
- Multi-purpose use for general mounting in printing industry.
- Joining of insulation materials.

### Technical Data

Liner	Siliconized PE coated paper – Havana
Carrier	Woven cloth - white
Adhesive	Synthetic rubber – white
Film Thickness	N/A
Adhesive Thickness	N/A
Total Thickness Allowance (Variance)	+/- 10%
Application Temperature	20 - 25°C
Temperature Resistance	60°C
Shear Strength	N/A
180° Peel Adhesion (ASTM D 3330)* (Steel)	≥15N/25mm
Holding Power (ASTM D 3654)*	>48 hours
Tensile Strength (ASTM D 3759)*	≥75N/25mm
Elongation (ASTM D 3759)*	≤10%
Initial Tack (JIS Z0237)*	N/A
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Cool, dry area out of direct sunlight – 12 months