



**Product:** Double Sided HM RDA

**Code:** D049

### Product Description

An OPP material, coated on both sides with a modified rubber adhesive.

### Features

- High initial tack.
- \*\*\* temperature range.
- Long life adhesive.
- Good transparency.

### Applications

- Ideally suited for plastic and metal nameplate mounting.
- Print finishing of cosmetic packaging, joining of leather, PVC films, fabric jointing, high value PE and Paper Bags
- Felt / foam bonding and laminating.

### Technical Data

Liner	Silicone paper – White (90gsm)
Carrier	OPP – clear
Adhesive	Modified rubber
Film Thickness	25 Micron
Adhesive Thickness	60g/m <sup>2</sup>
Total Thickness Allowance (Variance)	+/- 10%
Application Temperature	6° - 40°C
Temperature Resistance	-15° to 75°C
Sheer Strength	N/A
180° Peel Adhesion (ASTM D 3330)* (Steel)	18N/25mm
Holding Power (ASTM D 3654)*	≥120mins
Tensile Strength (ASTM D 3759)*	20N/cm
Elongation (ASTM D 3759)*	17%
Initial Tack (JIS Z0237)*	≤100mm
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Cool, dry area out of direct sunlight – 12 months