



**Product:** HBS Protection Film 75 Mic

**Code:** E026

### Product Description

A black and white co-extruded polyethylene protective UV laser film custom printed HBS.

### Features

- Protects surfaces from abrasion, corrosion, dirt and contamination during storage or in production.
- Stable adhesion ensures edges do not lift in wind but allows clean removal even after sunlight exposure.
- Strong film properties resist tearing and the solvent acrylic adhesive ensures good moisture resistance, and good adhesion even to textured surfaces.
- Exterior ageing for periods up to 6 months.

### Applications

- Temporary protection of many metals, plastics, glass and painted surfaces.
- Protection against dirt and damage during processing, storage and mounting.

### Technical Data

Liner	N/A
Carrier	White (outside) / Black (inside) Co-Ex Polyethylene
Adhesive	Water based Acrylic
Film Thickness	70 Micron
Adhesive Thickness	5 Micron
Total Thickness Allowance (Variance)	+/- 10%
Application Temperature	10° to 40°C
Temperature Resistance	75°C (maximum)
Shear Strength	N/A
180° Peel Adhesion (ASTM D 3330)* (Steel)	120 +/- 15g/cm
Holding Power (ASTM D 3654)*	N/A
Tensile Strength (ASTM D 3759)*	6MPa
Elongation (ASTM D 3759)*	>200%
Initial Tack (JIS Z0237)*	N/A
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Room temperature < 40°C; storage above 40°C may cause blocking of the rolls, therefore outside storage and direct sunlight should be avoided. Storage time max. 6 months after date of production



JOHANNESBURG - Tel: 011 975 0530  
CAPE TOWN - Tel: 021 703 2340



JOHANNESBURG (Head Office)  
10 Forge Road, Spartan, Kempton Park  
CAPE TOWN  
32 12th Street, Elsies River



Company Reg. No. : 1983/002184/07  
VAT No. : 4440192302



[www.easitape.co.za](http://www.easitape.co.za)