



**Product:** Masking Tape 60°

**Code:** M004

### Product Description

A pressure-sensitive *tape* made of a thin and easy-to-tear paper, and an easily released pressure-sensitive adhesive.

### Features

- The adhesive is the key element to its usefulness, as it allows the tape to be easily removed without leaving residue or damaging the surface to which it is applied.

### Applications

- Car repair painting, in-door paint masking, light duty packaging, bundling, holding, splicing and tabbing and other non-critical applications.

### Technical Data

Liner	N/A
Carrier	Crepe Paper – Cream
Adhesive	Solvent Rubber
Total Thickness	130 Micron
Total Thickness Allowance (Variance)	+/- 10%
Application Temperature	10 - 30°C
Temperature Resistance	60°C, 30mins
Sheer Strength	N/A
180° Peel Adhesion (ASTM D 3330)* (Steel)	≥4.5N/20mm
Holding Power (ASTM D 3654)*	≥10hrs
Tensile Strength (ASTM D 3759)*	≥75N/20mm
Elongation (ASTM D 3759)*	≤10%
Initial Tack (JIS Z0237)*	>29#(ball) /20mm
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Cool, dry area away from direct sunlight – 12 months