



**Product:** Sure Seal Packaging

**Code:** P023

## Product Description

A conformable polycoated Kraft backing with an aggressive rubber adhesive.

## Features

- Suitable for hand and automated machine applications (Easy release).
- Tamper evident – can't be reapplied or over taped due to its security release coating.
- Heat and moisture resistant.
- Suitable for use in deep freeze conditions after applications.
- Long adhesive life, UV and temperature resistant.

## Applications

- Security sealing of boxes and other demanding applications.
- Reel ends of paper, medium temperature splicing application.

## Technical Data

Liner	N/A
Carrier	Polycoated Kraft Paper
Adhesive	Synthetic Rubber
Film Thickness	80 GSM
Adhesive Thickness	30 GSM
Total Thickness Allowance (Variance)	+/- 5%
Application Temperature	15°-35°C
Temperature Resistance	95°C
Sheer Strength	N/A
180° Peel Adhesion (ASTM D 3330)* (Steel)	30N/25mm <sup>2</sup>
Holding Power (ASTM D 3654)*	N/A
Tensile Strength (ASTM D 3759)*	55N/cm
Elongation (ASTM D 3759)*	2-5%
Initial Tack (JIS Z0237)*	N/A
*Data represents the minimum value from the results of a series of tests	
Storage Conditions	Cool, dry area away from direct sunlight – 12 months